



PANTHERA U Trinocular



Optical System Colour Corrected Infinity Optical System (CCIS®)

Observation Tube Trinocular head, Siedentopf type

Interpupillary distance (mm) 48-75

Trino light split 50/50 fixed

Inclination 25° inclined, 360° swivelling

Eyepieces UC-WF10X/22

Eyepieces diopter adjustment +/- 5 dpt

Nosepiece Reversed quintuple, coded

Objective classification Plan UC Achromat objectives (Pb free)

Objectives $4X/0.1 \text{ (WD } 30.5 \text{mm)}, \ 10X/0.25 \text{ (WD } 17.4 \text{mm)}, \ 40X/0.65/S \text{ (WD } 0.6 \text{mm)},$

100X/1.25/S-Oil (WD 0.16mm)

Objective mounting thread W 4/5" x 1/36" (RMS standard)

Stage Compact and rackless stage

 Stage size (mm)
 185x145

 Travel range X&Y (mm)
 75x50

Upper limit stop Preset; adjustable

Condenser N.A. 0.90 / 1.25 Abbe condenser with slider slot

Focus mechanism Coaxial; tension adjustment

Minimum fine focus precision (µm) 2

Z-axis movement (mm) 25

Illumination type 3W LED, fixed Koehler

Illumination interchangeability LED color temperature interchangeability

Illumination features Motic LightTracer: Light memory, sleep mode (auto on-off), nosepiece LED light intensity

and mode indicator

Connectivity USB for external camera power

Power supply 110-240V (CE)

Accessories included Immersion oil 5ml, power cord, dust cover, allen key

Dimensions L x W x H (mm) 282x210x396

Weight (Kg) 8,3