Pen type, all in one, IP-67 **SALT METER** Model : DSA 211 ISO 0001 (

Model : PSA-311

ISO-9001, CE, IEC1010

Gİ.

UKAS QUALITY MANAGEMENT





Pen type, all in one, IP-67

SALT METER

Model : PSA-311

FEATURES

* The pen type, all in one Salt meter provides fast, accurate readings, with digital readability and easy operation.

* Measuring range : 0 to 12 % salt (% weight).

* Build in temperature sensor, ATC (auto temperature compensation)

* Carbon rod electrode for long life.

* IP67, water proof and protection.

* LCD display, read. to read.

* Data hold function for freezing the desired value.

* Auto power off to save the battery life.

* Records max. and min. value with recall.

* Microcomputer circuit, intelligent function, high accuracy.

* Compact size, light weight.

* Built-in Low battery indicator.

* Power supply by DC 1.5 V battery (UM4/AAA) x 4 PCs.

* Application : Water conditioning. aquarium, food processing, photography, school, laboratory, industrial and quality control.

SPECIFICATIONS	
Display	LCD, size : 20 mm x 28 mm.
Measurement Range	0 to 12 % salt (% weight).
Resolution	0.01 % salt.
Accuracy	0.5 % salt value
, loodi doj	
Temperature	* <i>F.S. : full scale.</i> * $23 \pm 5^{\circ}$ Automatic, 0 to 50 °C (32 to 122 °F).
Compensation	
Probe Structure	Carbon rod electrode for long life.
Data Hold	Freeze the display reading.
Memory Recall	Maximum & Minimum value.
Sampling Time	Approx. 0.8 second.
Circuit	Custom one-chip of microprocessor LSI circuit.
Power off	Auto shut off saves battery life or manual off by
	push button.
	* Power will off automatically after 10 min., if no
	button be pressed.
Operating Temp.	0 to 50 °C (32 to 140 °F).
Operating Humidity	Less than 80% RH.
Power Supply	DC 1.5V battery (UM-4/AAA) x 4 PCs.
Power Consumption	Approx. 5.7 mA.
Dimension	190 x 40 x 40 mm (7.5 x 1.6 x 1.6 inch).
Weight	171 g/0.38 LB.
Standard Accessories	Instruction Manual 1 PC
Optional	 * Soft carrying case with sash
Accessories	(210 x 80 x 50 mm), Model : CA-52A
	* Hard carrying case
	(280 x 195 x 65 mm), Model : CA-06

* Appearance and specifications listed in this brochure are subject to change without notice.